




Gellner Industrial, LLC
105 Tide Road, Hometown, PA 18252
PHONE: 570-668-8800
www.gellnerindustrial.com
water based industrial polymers



Ottopol SX-100 Technical Data sheet

Product Specifications

Description ---- Self Cross-linking Acrylic Emulsion	Appearance----- Translucent Emulsion
Solids-----41.0 - 43.0%	Specific Gravity -----1.0552
pH----- 8.0 - 9.0	Weight/Gallon -----8.80
Viscosity ----- 500 - 1500 cps	Freeze Thaw Stability ----- Keep from Freezing
Flash Point----- Same as Water	FDA Status ----- None
Glass Transition Temperature ----- 50 Degrees C	USDA Status----- None

ALKALI RESISTANCE

The dry resin is resistant to alkali with the use of an internal cross-linking mechanism. Inks and coatings will not be effected by the high pH of the detergent cleaner. The polymer will exhibit resistance to solvents, such as diluted alcohol solutions.

ADHESION TO SUBSTRATES

Inks and coatings have exceptionally good adhesion to vinyl and other non-porous substrates that require a hard film.

BLOCK and SCUFF RESISTANCE

Due to internally cross-linked mechanism block resistance and scuff is improved over conventional vehicles

IMPROVED FLOW, LEVELING & OPEN TIME

The SX-100 provides excellent resolubility properties for flexo and gravure printing applications. The flow and leveling characteristics will provide a high gloss finish. The resin provides non-curling properties on paper.

All product information contained in our product literature as well as any suggestions for use of our products contained in that literature, is based on information we believe to be reliable. However since particular conditions and methods of use involved in a particular product application are beyond our control, any such information is to be regarded as merely suggestive and should be verified by each user. Any suggestion made regarding the use of our products should not be construed as any authorization to infringe on patents, trademarks or similar rights of others.

Gellner Industrial, LLC warrants that its products have been manufactured with due care, are free of defects in material or workmanship, and conform to the specifications stated in the data sheets applicable to each product or to specifications otherwise explicitly agreed upon in a writing which refers to this warranty. THIS WARRANTY IS IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE. Gellner Industrial, LLC liability under this warranty is limited to replacing, free of charge, any product that is found upon examination by Gellner Industrial, LLC to be defective. Gellner Industrial, LLC SPECIFICALLY DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL DAMAGES. It is strongly recommended that a prospective user of one of our products verify the suitability of that product for a given application before its use in production.